



PrimoAire

Made by a HVAC Owner
for HVAC Contractors!



Available in White

PrimoAire Home IAQ Monitor

IAQ monitor Mount on Customer's wall or on a Tabletop and sends the sensor reading to the contractor's Primo Portal where the contractor can monitor the air in customer's home.

Designed for HVAC professionals to offer unique add on services to their business. A must for service trucks!

Features

- ◆ Mount on wall or set on tabletop.
- ◆ Dual Power Options - 24vac or 115vac USB-Micro cable.
- ◆ Pairs with home wi-fi for remote monitoring.
- ◆ Send customer's Air Quality data directly to contractor's PrimoPortal.
- ◆ Mobile App for technician to install and connect to customer's home.
- ◆ Humidity, Co2, VOC, Dust (pm2.5) & Temperature Monitoring.
- ◆ Green, Yellow & Red air quality indicator lights.
- ◆ Day, week & month air quality history.
- ◆ Monitor notifies contractor if power or internet connection is lost.
- ◆ Invite your customers to receive custom IAQ notification by email.
- ◆ Integrates with PrimoAire Hublay to control most air quality devices.

SPECIFICATIONS

SKU#

7WM1V01250

ELECTRICAL

24vac (shared from t-stat)
or
115vac Adaptor usb-c 5vdc 2A

DIMENSIONS

4-7/8" x 3-5/8" x 2"

SENSORS

Temperature Range- 40 -125F Accuracy 1.8 F
Humidity Range 1%-99% RH Accuracy 1.5%
CO2 Range 400 -20k ppm Accuracy 70ppm 3%
PM2.5 Range 0-1,000ug/m3 Accuracy 15ug/m3
VOC Range 1-500 Index Device Variance<15

WEIGHT

7.1 oz

Wi-Fi

2.4 GHz

WARRANTY

3-Years part

STORAGE

-20 F to 130 F (-0 C to 54 C)
0% -90% RH non-condensing

OPERATING HUMIDITY

90% non-condensing max

OPERATING AMBIENT

32 F to 105 F (-0 C to 41 C)

